## AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An interior trim component for a vehicle, said trim component comprising:

a body; and

an article holder removably mounted to said body, said article holder having a support structure for supporting an article, said article holder pivotally connected to said body and movable between a storage position and a deployed position, wherein in the deployed position said support structure of said article holder is higher relative to a position of said support structure when said article holder is in the storage position, and wherein said article holder is removably mounted to said body when in the deployed position.

- 2. (Cancelled)
- 3. (Original) The interior trim component according to Claim 1, wherein said body is an interior vehicle trim panel.
- 4. (Original) The interior trim component according to Claim 1, wherein said body includes a forward end and a rearward end, and said article holder is pivotally connected adjacent said forward end of said body.
- 5. (Original) The interior trim component according to Claim 4, wherein said forward end of said body includes a recess, and wherein at least a portion of said article holder is disposed within said recess when said article holder is in the storage position.
- 6. (Original) The interior trim component according to Claim 4, wherein said body defines a vehicle console.

- 7. (Previously Presented) The interior trim component according to Claim 1, wherein said body includes a lid.
- 8. (Original) The interior trim component according to Claim 7, wherein said lid is pivotally connected to said body.
- 9. (Original) The interior trim component according to Claim 8, wherein said lid is pivotally connected adjacent a rearward end of said body.
- 10. (Original) The interior trim component according to Claim 7, wherein said lid defines an armrest.
- 11. (Original) The interior trim component according to Claim 7, wherein in the deployed position said article holder is releasably connected to said lid, such that when said article holder is in the deployed position, movement of said lid causes said article holder to move.
- 12. (Original) The interior trim component according to Claim 1, wherein in the deployed position said support structure is forward relative to a position of said support structure when said article holder is in the storage position.
- 13. (Original) The interior trim component according to Claim 1, wherein said support structure includes a wall defining a cavity for supporting an article.
- 14. (Original) The interior trim component according to Claim 1, wherein said support structure is a clip for securing an article to said article holder.
- 15. (Original) The interior trim component according to Claim 14, wherein said clip is spring biased.

- 16. (Original) The interior trim component according to Claim 1, further including a latching mechanism for releasably latching said article holder in the deployed position.
- 17. (Original) The interior trim component according to Claim 16, wherein said latching mechanism is disposed between said body and said article holder.
- 18. (Original) The interior trim component according to Claim 16, wherein said latching mechanism comprises a latch extending outwardly from said article holder, and wherein said body includes an aperture for receiving said latch.
- 19. (Currently Amended) A console assembly for a vehicle, said console assembly comprising:

a console body having a lid, said lid pivotally connected to said console body; and

an article holder removably mounted to said console body, said article holder, having a support structure for supporting an article;

wherein said article holder is pivotally connected to said console body and movable between a storage position and a deployed position;

wherein in the deployed position, of said support structure of said article holder is higher relative to a position of said support structure when said article holder is in the storage position;

wherein said article holder is removably mounted to said console body when in the deployed position; and

wherein in the deployed position said article holder is releasably connected to said lid, such that when said article holder is in the deployed position, movement of said lid causes said article holder to move.

## 20. (Cancelled)

Attorney Docket No. 1-74748

(Currently Amended) An interior trim component for a vehicle 21. comprising:

a body;

a lid supported on said body for movement between first and second lid positions; and

an article holder supported on said body for movement between first and second article holder positions, said article holder being selectively engageable with said lid for movement therewith between said first and second article holder lid positions.

(New) An interior trim component for a vehicle, said trim component 22. comprising:

a body; and

an article holder removably mounted to said body, said article holder having a clip for securing an article to said article holder, said article holder pivotally connected to said body and movable between a storage position and a deployed position, wherein in the deployed position said clip of said article holder is higher relative to a position of said clip when said article holder is in the storage position.

(New) The interior trim component according to Claim 22, wherein said 23. clip is spring biased.

(New) An interior trim component for a vehicle, said trim component 24. comprising:

a body;

an article holder removably mounted to said body, said article holder having a support structure for supporting an article, said article holder pivotally connected to said body and movable between a storage position and a deployed position, wherein in the deployed position said support structure of said article holder is higher relative to a position of said support structure when said article holder is in the storage position; and

a latching mechanism for releasably latching said article holder in the deployed position.

- (New) The interior trim component according to Claim 24, wherein said 25. latching mechanism is disposed between said body and said article holder.
- (New) The interior trim component according to Claim 24, wherein said 26. latching mechanism comprises a latch extending outwardly from said article holder, and wherein said body includes an aperture for receiving said latch.